

IECHOTECH HP Ink Plotter



Parameters:

| Model | Iechotech InkJet-183 | Iechotech InkJet-220 |
|------------------------------|----------------------------|----------------------------|
| Maximum datum width | 188cm | 225cm |
| Effective print width | 183cm | 220cm |
| Number of Print head | 2 | 2 |
| Maximum printing speed | 60 M2 /hour | 70 M2/hour |
| Resolution | 150dpi | 150dpi |
| Model of print head | 51645a | 51645a |
| Add ink | repeated add ink | repeated add ink |
| Orienting method | Light Curtains | Light Curtains |
| Control system | Servo + step | Servo + step |
| Paper insert | Paper roll | Paper roll |
| Maximum weight of paper roll | 50kg | 50kg |
| Paper | 25g-65g | 25g-65g |
| Gross weight | 95kg | 115kg |
| Net weight | 55kg | 60kg |
| Output | Output Center | Output Center |
| Hardware interface | USB 2.0 | USB 2.0 |
| Doc. format | HPG/HPGL2/DMPL/DXF | HPG/ HPGL2/DMPL/DXF |
| Voltage of power | Electric circuit 220V/110V | Electric circuit 220V/110V |
| Frequency of power | 50Hz/60Hz | 50Hz/60Hz |
| Working temperature | 5°C~50°C | 5°C~50°C |
| Store temperature | -15°C~65°C | -15°C~65°C |
| Environment humidity | 0%~95% | 0%~95% |
| Safety standard | Up to UL1950 | Up to UL1950 |